



# Safety Data Sheet

Page 1 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 1. Identification of the substance/preparation and of the company/undertaking

<b>1.1 Product identifier</b>	<b>Glue Seal Clear</b>
<b>Item number</b>	<b>T128</b>
<b>UFI</b>	2500-C0AX-M00N-XP4H
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	Glue Seal Clear is a one-component MS-Polymer for gluing and sealing many different materials.
<b>1.3 Details of the supplier of the safety data sheet</b>	GSON EUROPE AB
<b>Address</b>	Nastagatan 9 SE-70227 Örebro. Sweden
<b>Homepage</b>	<a href="http://www.gson.se">www.gson.se</a>
<b>E-mail</b>	<a href="mailto:info@gson.se">info@gson.se</a>
<b>Telephone</b>	+46(0)19-185545
<b>1.4 Emergency telephone number</b>	For poison information call, NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales), in emergencies call 999.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification CLP (1272/2008/EC)

Hazardous to the aquatic environment - Chronic Hazard, Category 3; H412

EUH208

#### 2.2 Label elements

##### Pictogram

None

**Signal Word:** None

#### Contents

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate

#### Hazard statement Code(s)

H412 Harmful to aquatic life with long lasting effects.

#### Supplemental hazard information

EUH208: Contains N-(3-(trimethoxysilyl) propyl)ethylenediamine, Trimethoxyvinylsilane. May produce an allergic reaction.

#### Precautionary statements

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P273: Avoid release to the environment.

P501: Dispose of contents/container to an authorized waste treatment plant in accordance with local/national regulation.



# Safety Data Sheet

Page 2 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 2: Hazards identification (...)

#### 2.3 Other hazards

This product is not considered to contain a substances that meets the criteria for classification as PBT or vPvB substance.

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0.1\%$ .

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Components	CAS-No EC-No Reg-No	Conc.%	Hazard Class & Category Code*	Hazard statement Code(s)*
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3 217-164-6 01-2119970215-39	<1	Eye Dam. 1 Skin Sens. 1 Acute Tox. 4 STOT RE 2	H318 H317 H332 H373
Trimethoxyvinylsilane Index: 014-049-00-0	2768-02-7 220-449-8 01-2119513215-52	<1	Flam. Liq. 3 Acute Tox 4 Skin Sens. 1B	H226 H332 H317
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate	63843-89-0 264-513-3 01-2119978231-37	<1	Acute Tox. 4 STOT RE 2 Aquatic Chronic 1 M=10	H302 H373 H410
Methanol Index: 603-001-00	67-56-1 200-659-6 01-2119433307-44	<1	Flam. Liq. 2 Acute Tox. 3 Acute Tox. 3 Acute Tox. 3 STOT SE 1	H225 H301 H311 H331 H370

\* The full text of Hazard statement Codes are listed under section 16.

Substance	Specific concentration limits and acute toxicity estimates (ATE):
Methanol (67-56-1)	STOT SE 1; H370: $C \geq 10\%$ STOT SE 2; H371: $3\% \leq C < 10\%$

#### ATE mix (calculated)

ATE Oral: >2000 mg/kg  
ATE Dermal: >2000 mg/kg  
ATE Inhalation (ångor) 4h: >20 mg/l

The classification is based on data from the chemical supplier and [www.echa.europa.eu](http://www.echa.europa.eu) (databases)



# Safety Data Sheet

Page 3 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give fluids or induce vomiting if patient is unconscious. Keep person warm and calm.

##### Inhalation

Fresh air and rest. Contact a doctor if the complaints persist.

##### Skin contact

Immediately, take off all contaminated clothing. Wash with soap and water and rinse skin thoroughly. Contact a doctor if the complaints persist.

##### Eye contact

Rinse with lukewarm water for several minutes. Hold eyelids apart. Remove contact lenses, if present and easy to do. Contact a doctor if the complaints persist.

##### Ingestion

Do not provoke vomiting. Rinse mouth with water and drink several glasses of water. Go to hospital/doctor.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Inhalation:

May be irritating by inhalation. (Irritations, cough).

##### Skin contact:

May be irritating at skin contact (Pain, redness). Contains a substance which may cause allergies in skin contact for sensitive persons.

##### Eye contact:

May be irritating to eyes. (Pain, redness)

##### Ingestion:

Ingestion may cause discomfort.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Not flammable. Select extinguishing media appropriate to surrounding fire. Preferably ABC Powder.

#### 5.2 Special hazards arising from the substance or mixture

Do not breath fumes as during fire, thick smoke and hazardous fumes may be formed.

#### 5.3 Advice for firefighters

Use an appropriate breathing apparatus and protective suits.

##### Additional information

Cool endangered containers with water in case of fire. Move containers from fire area if it can be done without risk.

Fire residues and contaminated water should be disposed of in accordance with local regulations.

Avoid release to the environment.



# Safety Data Sheet

Page 4 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Follow handling instructions.

Ensure adequate ventilation.

Remove all sources of ignition and eliminate electrostatic charges.

Prevent the formation of flammable vapor-air mixtures, either through ventilation or the use of an inert medium

Keep unauthorized and unprotected persons at a safe distance.

#### 6.2 Environmental precautions

Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Re-use product if possible. Small quantities may be wiped up with a cloth. Contain larger spill with inert material. Absorb in vermiculite or dry sand.

#### 6.4 Reference to other sections

See section 7 for proper handling and storage.

For personal protection see section 8.

Collected waste is placed in closed metal containers and disposed of as waste according to section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Use personal protective equipment. Follow handling instructions.

Do not eat, drink or smoke when handling the product.

Ensure adequate ventilation.

Avoid evaporation of the product as it contains flammable substances which can form flammable vapour/air mixtures in the presence of ignition sources.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store tightly closed at temperatures between 5 - 30 ° C.

Store the product tightly closed in a dry, cool and well-ventilated area.

Always store the product in the same material as the original material on the package.

Store away from sources of ignition, sparks, sunlight, static electricity and foodstuffs.

#### 7.3 Specific end use(s)

-



# Safety Data Sheet

According to Regulation (EC) No. 1907/2006 annex II and EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Appropriate engineering controls

Provide adequate ventilation

Provide eyewash station.

##### Swedish limit values or limit values according to the European commission

Substance	CAS number	Long-term exposure limit	Short-term exposure limit	Comments:
Methanol	67-56-1	200 ppm 250 mg/m <sup>3</sup>	250 ppm 350 mg/m <sup>3</sup>	H, V 23

##### Explanation of Comments:

H - The substance is readily absorbed through the skin. The limit value is considered to provide sufficient protection if the skin is protected.

V - Indicative short-term exposure limit value to be used as a recommended maximum value that should not be exceeded.

23 - The substance has an indicative EU limit value.

##### British limit values (EH40/2005 Workplace exposure limits)

Substance	CAS number	Long-term exposure limit	Short-term exposure limit	Comments
Methanol	67-56-1	200 ppm 266 mg/m <sup>3</sup>	250 ppm 333 mg/m <sup>3</sup>	Sk

##### Explanation of Comments:

Sk - Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

#### DNEL

<b>Trimethoxyvinylsilane (2768-02-7)</b>	Long-term exposure – Employees Systematic effects, Dermal: 3.9 mg/kg Long-term exposure – Employees Systematic effects, Inhalation; 27.6 mg/m <sup>3</sup> Long-term exposure – Consumers Systematic effects, Oral: 0.3 mg/kg Long-term exposure – Consumers Systematic effects, Dermal: 7.8 mg/kg Long-term exposure – Consumers Systematic effects, Inhalation: 18.9 mg/m <sup>3</sup>
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)</b>	Long-term exposure – Employees Systemic effects, Dermal; 0.07 mg/kg Long-term exposure – Employees Systemic effects, Inhalation; 0.05 mg/m <sup>3</sup> Long-term exposure – Consumers Systemic effects, Oral: 0.03 mg/kg Long-term exposure – Consumers Systemic effects, Dermal: 0.33 mg/kg



# Safety Data Sheet

According to Regulation (EC) No. 1907/2006 annex II and EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

**SECTION 8: Exposure controls/personal protection (...)**

	Long-term exposure – Consumers Systemic effects, Inhalation; 0.01 mg/m <sup>3</sup>
<b>Methanol (67-56-1)</b>	Short-term exposure – Employees Systemic effects, Dermal; 20 mg/kg Short-term exposure – Employees Systemic effects, Inhalation; 130 mg/m <sup>3</sup> Short-term exposure – Employees Local effects, Inhalation; 130 mg/m <sup>3</sup> Long-term exposure – Consumers Systemic effects, Dermal; 20 mg/kg Long-term exposure – Consumers Systemic effects, Inhalation; 130 mg/m <sup>3</sup> Long-term exposure – Consumers Local effects, Inhalation; 130 mg/m <sup>3</sup> Short-term exposure – Consumers Systemic effects, Oral; 4 mg/kg Short-term exposure – Consumers Systemic effects, Dermal; 4 mg/kg Short-term exposure – Consumers Systemic effects, Inhalation; 26 mg/m <sup>3</sup> Short-term exposure – Consumers Local effects, Inhalation; 26 mg/m <sup>3</sup> Long-term exposure – Consumers Systemic effects, Oral; 4 mg/kg Long-term exposure – Consumers Systemic effects, Dermal; 4 mg/kg Long-term exposure – Consumers Systemic effects, Inhalation; 26 mg/m <sup>3</sup> Long-term exposure – Consumers Local effects, Inhalation; 26 mg/m <sup>3</sup>

### PNEC

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	25 mg/l	STP
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.009 mg/kg	Soil
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.62 mg/l	Intermittent releases
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.062 mg/l	Freshwater
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.006 mg/l	Saltwater
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.22 mg/kg	Sediment(freshwater)
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.022 mg/kg	Sediment (saltwater)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	1 mg/l	STP
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	1 mg/kg	Soil



# Safety Data Sheet

Page 7 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 8: Exposure controls/personal protection (...)

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	0.61 mg/l	Intermittent releases
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	0 mg/l	Freshwater
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	0 mg/l	Saltwater
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	504.4 mg/kg	Sediment(freshwater)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	50.44 mg/kg	Sediment (saltwater)
Methanol (67-56-1)	100 mg/l	STP
Methanol (67-56-1)	100 mg/kg	Soil
Methanol (67-56-1)	1540 mg/l	Intermittent releases
Methanol (67-56-1)	20.8 mg/l	Freshwater
Methanol (67-56-1)	2.08 mg/l	Saltwater
Methanol (67-56-1)	77 mg/kg	Sediment(freshwater)
Methanol (67-56-1)	7.7 mg/kg	Sediment (saltwater)

### 8.2 Exposure controls

#### General protective and hygiene measures

Wash hands before breaks and after work.

The usual precautionary measures for the handling of chemicals have to be observed.

#### Individual protection measures, such as personal protective equipment

Always consult a competent person/supplier when selecting personal protective equipment

#### Respiratory protection

In case of insufficient ventilation or if there is a risk of inhalation of spray mist, wear suitable respiratory equipment.

#### Hand protection

Use chemical-resistant protective gloves (e.g. Butyl rubber) EN 374-1:2016, Type B

#### Eye protection

Wear protective goggles if there is a risk of splash, EN 166

#### Body protection

Wear suitable protective clothing. EN 14605 Type 4

Wear non-slip work shoes. EN 14605 Type 4



# Safety Data Sheet

Page 8 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colorless
Odour	Not determined
Melting point/freezing point (°C):	Not determined
Boiling point or initial boiling point and boiling range (°C)	376 °C
Flammability (°C)	Not determined
Lower and upper explosion limit	Not determined
Flash point (°C):	>60 °C
Auto-ignition temperature (°C)	224 °C
Decomposition temperature (°C)	Not determined
pH	Not determined
Kinematic viscosity	Not determined
Solubility	Not determined
Partition coefficient n-octanol/water (log value)	Not determined
Vapour pressure	28 Pa (20 °C) 131.72 Pa / 0.13 kPa (50 °C)
Density and/or relative density	1065.8 kg/m <sup>3</sup>
Relative vapour density	1.066 (20 °C)
Particle characteristics	Not relevant. The product is a liquid.

#### 9.2 Other information

V.O.C. (Supply): 1.02 % weight  
V.O.C. density at 20 °C: 10.92 kg/m<sup>3</sup> (10.92 g/l)  
Average carbon number: 5.98  
Average molecular weight: 178.17 g/mol

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Stable under recommended storage and handling conditions.

#### 10.2 Chemical stability

Stable under recommended storage and handling conditions.

#### 10.3 Possibility of hazardous reactions

None known.

#### 10.4 Conditions to avoid

Avoid direct sunlight, high temperatures.

#### 10.5 Incompatible materials

Avoid strong acids, strong alkalis and strong bases.

#### 10.6 Hazardous decomposition products

None known.



## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

See section 4 as well. (Most important symptoms and effects, both acute and delayed)

##### Irritating/Corrosive properties

Not classified as irritating / corrosive according to CLP.

##### Acute toxic

Not classified as acute toxic according to CLP.

##### Toxicology data

Information/data about this preparation is not available.

#### Toxicological data from animal experiments regarding relevant constituent substances:

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	LD <sub>50</sub> Oral rat: 2295 mg/kg
Trimethoxyvinylsilane (2768-02-7)	LD <sub>50</sub> Dermal rabbit: 3870 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)	LD <sub>50</sub> Oral rat: 1490 mg/kg LD <sub>50</sub> Dermal rabbit: 3170 mg/kg
Methanol (67-56-1)	LD <sub>50</sub> Oral: 100 mg/kg LD <sub>50</sub> Dermal: 300 mg/kg

#### STOT-single exposure -repeated exposure.

No known

#### Routes of exposure

Inhalation, eyes and skin (ingestion).

#### Allergenic potential

This product is not classified as allergenic by inhalation or skin contact but it contains a small amount of N-(3-(trimethoxysilyl) propyl)ethylenediamine & Trimethoxyvinylsilane which may cause an allergic reaction in persons sensitive to these substances.

#### Carcinogenicity, mutagenicity and toxicity for reproduction

This product is not classified as carcinogen, mutagen and toxic for reproduction.

#### Aspiration hazard

None.

#### 11.2 Information on other hazards

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0.1\%$



## T128 Glue Seal Clear

**GSON EUROPE**

Revision date: 2025-10-09 Ver. 3

**SECTION 12: Ecological information**

This product is classified as dangerous for the environment. Harmful to aquatic life with long lasting effects.

Prevent uncontrolled discharges to the sewer system.

**12.1 Toxicity**

Information about this preparation is not available.

**Toxicology data for the containing components:**

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>	LC <sub>50</sub> Fish 96h: 597 mg/l Sp.: Brachydanio Rerio EC <sub>50</sub> Daphnia 48h: 81 mg/l Sp.: Daphnia magna EC <sub>50</sub> Algae 72h: 8.8 mg/l Sp.: Selenastrium capricornutum
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate (63843-89-0)</b>	LC <sub>50</sub> Fish 96h: >0.1 - 1 mg/l EC <sub>50</sub> Daphnia 48h: >0.1 - 1 mg/l EC <sub>50</sub> Algae 72h: >0.1 - 1 mg/l NOEC Daphnia: 0.002 mg/l Sp.: Daphnia magna
<b>Methanol (67-56-1)</b>	LC <sub>50</sub> Fish 96h: 15400 mg/l Sp.: Lepomis macrochirus EC <sub>50</sub> Daphnia 96h: 12000 mg/l Sp.: Nitrocraspinipes EC <sub>50</sub> Algae 168h: 530 mg/l Sp.: Microcystis aeruginosa NOEC Fish: 15800 mg/l Sp.: Oryzias latipes NOEC Daphnia: 122 mg/l Sp.: Daphnia magna

**12.2 Persistence and degradability**

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3) - 39% (28d)

Trimethoxyvinylsilane (2768-02-7) - 51% (28d) concentration: 104 mg/l

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butyl malonate (63843-89-0) - 2% (28d) concentration: 10 mg/l

Methanol (67-56-1) - 92% (14d) concentration: 100 mg/l. COD: 1.42 g O<sub>2</sub>/g

**12.3 Bioaccumulative potential**

Pow Log: -0.82 - Trimethoxyvinylsilane (2768-02-7)

Low potential for bioaccumulation. BCF: 3. Pow Log: -0.77 - Methanol (67-56-1)

**12.4 Mobility in soil**

Trimethoxyvinylsilane (2768-02-7) - high mobility. Koc: 0.95. Henry: 4.61E-1 Pa·m<sup>3</sup>/mol (too and moist soil.

Methanol (67-56-1) - Surface tension: 2.355E-2 N/m (25 °C)

**12.5 Results of PBT and vPvB assessment**

This product is not considered to contain a substances that meets the criteria for classification as PBT or vPvB substance.

**12.6 Endocrine disrupting properties**

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0.1\%$

**12.7 Other adverse effects**

No known.



# Safety Data Sheet

Page 11 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

This product or residues of this product are classified as hazardous waste.

Dispose of in accordance with local authority requirements.

**EWG- code:** Depends on line of business and use, for example:

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

#### Disposal of Packaging

Well cleaned packaging could be left for recycling

### SECTION 14: Transport information

The product is not classified as dangerous goods according to ADR/RID, IMDG, IATA\_DGR.

#### 14.1 UN number or ID number

-

#### 14.2 UN proper shipping name

-

#### 14.3 Transport hazard class(es)

-

#### 14.4 Packing group

-

#### 14.5 Environmental hazards

Marine Pollutant: No

#### 14.6 Special precautions for user

-

#### 14.7 Maritime transport in bulk according to IMO instruments

-

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification according to Regulation (EC) No. 1907/2006 annex II and EC/2020/878.  
EH40/2005.

Reach (1907/2006/EC)

Substances on the Candidate list (1907/2006 / EC) None.

Substances on the List of Permits Annex XIV by REACH: None

Substances of (1005/2009 EC) Substances that deplete the ozone layer: None.

Substances of Annex 1 528/2012 EC: None

Substances of 649/2012 Eg concerning import and export of dangerous chemical substances:  
None

#### List of Restrictions, Annex XVII to REACH:

Methanol (67-56-1) - entry: 69

Contains <0.1% 1,2-benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (68515-49-1) – entry: 52

#### 15.2 Chemical safety assessment

No conducted.



# Safety Data Sheet

Page 12 of 12

According to Regulation (EC) No. 1907/2006 annex II and  
EC/2020/878EC

## T128 Glue Seal Clear

GSON EUROPE

Revision date: 2025-10-09 Ver. 3

### SECTION 16: Other information

#### The full text of Hazard statement Codes listed under section 3

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

This information is provided for health and safety assessments by an industrial user. Reference should be made to any relevant local or national health, safety, and environmental legislation.

#### Sources

Safety data sheet provided by the manufacturer.

CLP-regulation, [www.kemi.se](http://www.kemi.se), EH40/2005. [www.echa.europa.eu](http://www.echa.europa.eu) (Databases)

#### Version 3: 2025-10-09

Safety data sheet according to Regulation (EC) No. 1907/2006 annex II and EC/2020/878.

#### Previous versions

Version 1: 2022-05-25

Version 2: 2025-10-02

#### Abbreviations explanations

ADR: International Carriage of Dangerous Goods by Road

BCF: Bio Concentration Factor

CAS-nr: Chemical Abstracts Service number

DNEL: Derived No Effect Level

EC<sub>50</sub>: Effect Concentration

EG-nr: A substance number i Eines, Elincs or in No-Longer Polymers List.

IMDG: International Maritime Dangerous Goods Code.

LC<sub>50</sub>: Lethal Concentration

LD<sub>50</sub>: Lethal Dose

IC<sub>50</sub>: Median Inhibition Concentration

NOEC: No Observed Effect Concentration

PBT-substance: Persistent, Bio accumulative and Toxic substances.

PNEC: Predicted No Effect Concentration

vPvB-substance: Very persistent and Very Bio accumulative substances.