



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 1. Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier	Glue Seal White
Item number	T134
UFI	UC00-C0QR-700N-8C9N
1.2 Relevant identified uses of the substance or mixture and uses advised against	Is a one-component MS-Polymer that is solvent-free. It both glues and seals most materials. Glue Seal can withstand both tension, pressure and vibration. Can also be overpainted.
1.3 Details of the supplier of the safety data sheet	GSON EUROPE AB
Address	Nastagatan 9 SE-70227 Örebro. Sweden
Homepage	www.gson.se
E-mail	info@gson.eu
Telephone	+46(0)19-185545
1.4 Emergency telephone number	Swedish poison information (in less acute cases during office hours) +46(0)10-4566700

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification CLP (1272/2008/EC)

EUH208

2.2 Label elements

Pictogram

None

Signal Word: None

Contents

-

Hazard statement Code(s)

None.

Supplemental hazard information

EUH208: Contains Trimethoxyvinylsilane, N-(3-(trimethoxysilyl) propyl)ethylenediamine. May produce an allergic reaction

Precautionary statements

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P501: Dispose of contents/container to an authorized waste treatment plant in accordance with local/national regulation.

2.3 Other hazards

This product is considered to contain a substances that meets the criteria for classification as PBT or vPvB substance: Bumetrizole

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Components	CAS-No EC-No Reg-No	Conc.%	Hazard Class & Category Code*	Hazard statement Code(s)*
Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]	13463-67-7 236-675-5 01-2119489379-17	2,5 - <5	-	-
Trimethoxyvinylsilane Index: 014-049-00-0	2768-02-7 220-449-8 01-2119513215-52	<1	Flam. Liq. 3 Acute Tox 4 Skin Sens. 1B	H226 H332 H317
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3 217-164-6 01-2119970215-39	<1	Eye Dam. 1 Skin Sens. 1 Acute Tox. 4 STOT RE 2	H318 H317 H332 H373
Bumetizole PBT/vPvB substance	3896-11-5 223-445-4 01-2119971796-18	<1	-	-
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9 258-207-9 01-2119537297-32	<1	Eye Dam. 1 Repr.2 Aquatic Acute 1 Aquatic Chronic 2	H318 H361f H400 H411

* The full text of Hazard statement Codes are listed under section 16.

ATE MIX

LD₅₀ Oral: >2000 mg/kg

LC₅₀ Dermal: >2000 mg/kg

LC₅₀ Inhalation Mist 4h: >20 mg/l

The classification is based on data from the chemical supplier and www.echa.europa.eu (databases)



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give fluids or induce vomiting if patient is unconscious. Keep person warm and calm.

Inhalation

Fresh air and rest. In case of difficulty breathing, give respiratory assistance and consult a doctor.

Skin contact

Immediately, take off all contaminated clothing wash with soap and water and rinse the skin thoroughly. Never use thinner or solvent. Contact a doctor if the complaints persist.

Eye contact

Rinse with lukewarm water for several minutes. Hold eyelids apart. Remove contact lenses, if present and easy to do. Contact a doctor if the complaints persist.

Ingestion

Rinse mouth with water and drink plenty of water. Go to hospital/doctor.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation:

May be irritating by inhalation. (Irritations, cough).

Skin contact:

May be irritating at skin contact (Pain, redness). Contains a substance which may cause allergies in skin contact for sensitive persons.

Eye contact:

May be irritating to eyes. (Pain, redness)

Ingestion:

Ingestion may cause discomfort.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Not flammable. Select extinguishing media appropriate to surrounding fire. For example Powder.

5.2 Special hazards arising from the substance or mixture

Do not breath fumes as during fire, thick smoke and hazardous fumes may be formed.

5.3 Advice for firefighters

Use an appropriate breathing apparatus and protective suites.

Additional information

Cool endangered containers with water in case of fire. Move containers from fire area if it can be done without risk.



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation, do not breathe spray or mist.

Prevent the formation of flammable vapor-air mixtures, either through ventilation or the use of an inert medium

Take precautionary measures against static discharges.

Remove all sparks and heat sources.

6.2 Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Re-use product if possible. Small quantities may be wiped up with a cloth. Contain larger spill with inert material. Absorb in vermiculite or dry sand.

6.4 Reference to other sections

See section 7 for proper handling and storage.

For personal protection see section 8.

Collected waste is placed in closed metal containers and disposed of as waste according to section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Follow handling instructions. Use personal protective equipment.

Avoid contact with skin and eyes.

Ensure adequate ventilation, do not breathe spray or mist.

7.2 Conditions for safe storage, including any incompatibilities

Store tightly closed at temperatures between 5 - 30 °C.

Store the product tightly closed in a dry, cool and well-ventilated area.

Store away from sources of ignition, sparks, sunlight, static electricity and foodstuffs.

Always store the product in the same material as the original material on the package.

7.3 Specific end use(s)

-

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Appropriate engineering controls

Provide adequate ventilation

Swedish limit values or limit values according to the European commission

Ämne	CAS-nr	NGV	KGV	Anm.
Titandioxid	13463-67-7			-
- Total dust		- 5 mg/m ³	- -	



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 8: Exposure controls/personal protection

British limit values (EH40/2005 Workplace exposure limits)

Substance	CAS number	Long-term exposure limit	Short-term exposure limit	Comments
Titanium dioxide total inhalable respirable	13463-67-7	10 mg/m ³ 4 mg/m ³	- -	-

DNEL

Trimethoxyvinylsilane (2768-02-7)	Long-term exposure – Employees Systematic effects, Dermal: 01.8 mg/kg Long-term exposure – Employees Systematic effects, Inhalation: 1.27 mg/m ³ Long-term exposure – Consumers Systematic effects, Oral: 0.18 mg/kg Long-term exposure – Consumers Systematic effects, Dermal: 0.9 mg/kg Long-term exposure – Consumers Systematic effects, Inhalation: 0.31 mg/m ³
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	Long-term exposure – Employees Systematic effects, Dermal: 01.8 mg/kg Long-term exposure – Employees Systematic effects, Inhalation: 1.27 mg/m ³ Long-term exposure – Consumers Systematic effects, Oral: 0.18 mg/kg Long-term exposure – Consumers Systematic effects, Dermal: 0.9 mg/kg Long-term exposure – Consumers Systematic effects, Inhalation: 0.31 mg/m ³

DNEL

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	25 mg/l	STP
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.009 mg/kg	Soil
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.62 mg/l	Intermittent releases
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.062 mg/l	Freshwater
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.0062 mg/l	Saltwater
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.22 mg/kg	Sediment freshwater)
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	0.02 mg/kg	Sediment (saltwater)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	1 mg/l	STP
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	1.18 mg/kg	Soil
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	0.007 mg/l	Intermittent releases
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	0.04 mg/l	Freshwater
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	0.0038 mg/l	Saltwater
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	5.9 mg/kg	Sediment(freshwater)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	0.59 mg/kg	Sediment (saltwater)



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

General protective and hygiene measures

Wash hands before breaks and after work.

The usual precautionary measures for the handling of chemicals have to be observed.

Individual protection measures, such as personal protective equipment

Always consult a competent person/supplier when selecting personal protective equipment

Respiratory protection

In case of insufficient ventilation or if there is a risk of inhalation of spray mist, wear suitable respiratory equipment.

Hand protection

Use chemical-resistant gloves. (For example Nitrilrubber, PVC) EN 420:2003+A1:2009.

Eye protection

Wear protective goggles if there is a risk of splash, EN 166:2001, EN 172:1994/A1:2000, EN 172:1994/A2:2001, EN ISO 4007:2012.

Body protection

Wear suitable protective clothing. EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

Wear non-slip work shoes. EN ISO 20345:2012, EN 13832-1:2007.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	White
Odour	Not determined
Melting point/freezing point	Not determined
Boiling point or initial boiling point and boiling range	340
Flammability	Not determined
Lower and upper explosion limit	Not determined
Flash point	>60
Auto-ignition temperature	224
Decomposition temperature	Not determined
pH	Not determined
Kinematic viscosity	Not determined
Solubility	Not determined
Partition coefficient n-octanol/water (log value)	Not determined
Vapour pressure	5 Pa 20 °C 39 Pa 50 °C
Density and/or relative density	1.548
Relative vapour density	Not determined
Particle characteristics	Not relevant. The product is a liquid.

9.2 Other information

V.O.C: 0.75% weight. V.O.C density: 11.61 kg/m³. Molmass: 179.3 g/mol



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions.

10.2 Chemical stability

Stable under recommended storage and handling conditions.

10.3 Possibility of hazardous reactions

None known.

10.4 Conditions to avoid

Avoid direct sunlight and high temperatures.

10.5 Incompatible materials

Strong acids, alkalis and strong bases.

10.6 Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

See section 4 as well. (Most important symptoms and effects, both acute and delayed)

Irritating/corrosive properties

Not classified as irritating / corrosive according to CLP.

Acute toxic

Not classified as acute toxic according to CLP.

Toxicology data

Information/data about this preparation is not available.

Toxicological data from animal experiments regarding relevant constituent substances:

Titaniumdioxid (13463-67-7)	LD ₅₀ Oral Rat: 10000 mg/kg LD ₅₀ Dermal Rabbit: 10000 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	LD ₅₀ Oral Rat: 2295 mg/kg
Trimethoxyvinylsilane (2768-02-7)	LD ₅₀ Dermal Rabbit: 3870 mg/kg
Bumetizole (3896-11-5)	LD ₅₀ Oral Rat: 5100 mg/kg
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	LD ₅₀ Oral Rat: 3700 mg/kg

STOT-single exposure -repeated exposure.

No known

Routes of exposure

Inhalation, eyes and skin (ingestion).

Allergenic potential

This product is not classified as allergenic by inhalation or skin contact but it contains a small amount of N-(3-(trimethoxysilyl)propyl)ethylenediamine & Trimethoxyvinylsilane which may cause an allergic reaction in persons sensitive to these substances.

Carcinogenicity, mutagenicity and toxicity for reproduction

This product is not classified as carcinogen, mutagen and toxic for reproduction.



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 11: Toxicological information

Aspiration hazard

None.

11.2 Information on other hazards

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$

SECTION 12: Ecological information

This product is not classified as dangerous for the environment.

Prevent uncontrolled discharges to the sewer system.

12.1 Toxicity

Information about this preparation is not available.

Toxicology data for the containing components:

Trimethoxyvinylsilane (2768-02-7)	LC ₅₀ Fish 96h: 191 mg/l Oncorhynchus mykiss EC ₅₀ Daphnia 48h: 167 mg/l EC ₅₀ Algea 72h: 957 mg/l NOEC Daphnia: 28.1 mg/l
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	LC ₅₀ Fish 96h: 597 mg/l Brachydanio Rerio EC ₅₀ Daphnia 48h: 81 mg/l EC ₅₀ Algea 72h: 8.8 mg/l Selenastrium capricornutum
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	LC ₅₀ Fish 96h: 5.3 mg/l Oryzias latipes EC ₅₀ Daphnia 48h: 8.6 mg/l EC ₅₀ Algea 72h: 8.8 mg/l Pseudokirchneriella subcapitata NOEC Daphnia: 0.23 mg/l
Bumetrizole (3896-11-5)	NOEC Daphnia 10 mg/l

12.2 Persistence and degradability

Trimethoxyvinylsilane (2768-02-7) – 51% at 28d.

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3) – 39% at 28d.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9) 29% at 28d

Bumetrizole (3896-11-5) – 0% at 28d.

12.3 Bioaccumulative potential

Trimethoxyvinylsilane (2768-02-7) – logPow: -0.82

Bumetrizole (3896-11-5) – BCF 895

12.4 Mobility in soil

Trimethoxyvinylsilane (2768-02-7) -Very high. KOC: 0,95.

12.5 Results of PBT and vPvB assessment

This product is considered to contain a substances that meets the criteria for classification as PBT or vPvB substance: Bumetrizole

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 12: Ecological information

12.7 Other adverse effects

No known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

This product or residues of this product are not classified as hazardous waste.

Dispose of in accordance with local authority requirements.

EWC- code: Depends on line of business and use, for example:

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09.

Disposal of Packaging

Well cleaned packaging could be left for recycling

SECTION 14: Transport information

The product is not classified as dangerous goods according to ADR/RID, IMDG, DGR.

14.1 UN number or ID number

-

14.2 UN proper shipping name

-

14.3 Transport hazard class(es)

-

14.4 Packing group

-

14.5 Environmental hazards

Marine Pollutant: No

14.6 Special precautions for user

-

14.7 Maritime transport in bulk according to IMO instruments

-



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification according to Regulation (EC) No. 1907/2006 annex II and EC/2020/878. EH40/2005.

Substances on the Candidate list (1907/2006 / EC) - Bumetrizole (3896-11-5): vPvB (Article 57e).

Substances on the List of Permits Annex XIV by REACH: None

Substances of (1005/2009 EC) Substances that deplete the ozone layer: None.

Substances of Annex 1 528/2012 EC: None

Substances of 649/2012 Eg concerning import and export of dangerous chemical substances: None

List of Restrictions, Annex XVII to REACH:

Contains 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich.

15.2 Chemical safety assessment

No conducted.

SECTION 16: Other information

The full text of Hazard statement Codes listed under section 3

H226 Flammable solid.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure .

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

This information is provided for health and safety assessments by an industrial user. Reference should be made to any relevant local or national health, safety, and environmental legislation.

Sources

Safety data sheet provided by the manufacturer.

CLP-regulation, www.kemi.se, EH40/2005. www.echa.europa.eu (Databases)

Version 3: 2025-10-02

Safety data sheet according to Regulation (EC) No. 1907/2006 annex II and EC/2020/878.

Previous versions

Version 1: 2013-04-30

Version 2: 2022-05-25.



T134 Glue Seal White

GSON EUROPE

Revision date: 2025-10-02 Ver.3

SECTION 16: Other information (...)

Abbreviations explanations

ADR: International Carriage of Dangerous Goods by Road

BCF: Bio Concentration Factor

CAS-nr: Chemical Abstracts Service number

DNEL: Derived No Effect Level

EC₅₀: Effect Concentration

EG-nr: A substance number i Einescs, Elincs or in No-Longer Polymers List.

IMDG: International Maritime Dangerous Goods Code.

LC₅₀: Lethal Concentration

LD₅₀: Lethal Dose

IC₅₀: Median Inhibition Concentration

NOEC: No Observed Effect Concentration

PBT-substance: Persistent, Bio accumulative and Toxic substances.

PNEC: Predicted No Effect Concentration

vPvB-substance: Very persistent and Very Bio accumulative substances.